



## PRODUCT DATA

**THALLIUM SX 15W40**  
**API SL**

**SEMI SYNTHETIC 4T**  
**MOTORCYCLE LUBRICANT**

## DESCRIPTION

**FleetOil THALLIUM Mx-15W-40** Engine Oil was specially developed for the demands of modern 4-stroke motorcycle engines. Selected mineral base oils in combination with state-of-the-art additive technology keep the lubricated components clean and ensure excellent protection of the engine and transmission against wear and corrosion.

## APPLICATION

**FleetOil THALLIUM Mx-15W-40** is suitable for motorcycles built in Europe and in Japan for which the JASO MA specifications are recommended. The unique, mineral oil formula exceeds the requirements of leading manufacturers and under normal operating conditions will provide full protection for your engine

## BENEFITS

- Classic multigrade oil with motorcycle-specific additives
- Optimal frictional properties prevent clutch slip
- Very good protection against residue build-up, wear and corrosion
- Suitable for viscosity range for all operating conditions
- Greater fuel efficiency

## PRODUCT PERFORMANCE CLAIM

**FleetOil THALLIUM Mx-15W-40** surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API SL
- CCMC G2-D1
- JASO MA

## TYPICAL CHARACTERISTICS

| NAME                 | METHOD     | UNIT   | THALLIUM MX 15W40 SL (SAE J 300) |
|----------------------|------------|--------|----------------------------------|
| Density @ 15°C       | ASTM D1298 | Kg/ltr | 0.885                            |
| Viscosity @ 100°C    | ASTM D445  | cSt    | 14.5                             |
| Viscosity @ 40°C     | ASTM D445  | cSt    | 143.0                            |
| Viscosity Index      | ASTM D2270 | None   | 143                              |
| Flash Point, minimum | ASTM D92   | °C     | 210                              |

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 | [www.radifleet.com.my](http://www.radifleet.com.my)