



## PRODUCT DATA

**ZYLIUM SAE 5W40  
API SN/CF : ACEA A3/B4**

**FULLY-SYNTHETIC LUBRICANT**

### DESCRIPTION

**FleetOil Zylum 5W-40, API SN/CF, ACEA A3/B4** is a premium fully synthetic and carefully engineered high performance engine oil formulated using the latest based oil and an advance additive technology to provide maximum worry-free engine protection, performance and superior oil drain interval. The oil has an adaptive strength to respond to your engines every need, giving it unique adaptive strength that reduces metal to metal contact across a range of different driving speeds, lowering friction and maximises engine performance.

### APPLICATION

**FleetOil Zylum 5W-40, API SN/CF, ACEA A3/B4** It provides maximum protection in engines operating under severe conditions, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected systems.

### BENEFITS

- Excellent high temperature protection, sludge and deposit control
- Excellent overall lubricant and wear protection
- Superior engine cleanliness and easy start-up

### PRODUCT PERFORMANCE CLAIM

**FleetOil Zylum 5W-40, API SN/CF, ACEA A3/B4** surpasses a wide range of specifications and is suitable where the following requirements are called for:

- API Petrol: SN, (SM, SL, SJ, SH and all superseded classifications) / API Diesel : CF
- ACEA A3/B4, High performance shear stable petrol/diesel engine oil
- MB 229.3 / VW 502/505

### TYPICAL CHARACTERISTICS

NAME	METHOD	UNIT	ZYLIUM 5W40 SN/CF : ACEA A3/B4 (SAE J 300)
Density @ 15°C	ASTM D1298	Kg/ltr	0.847
Viscosity @ 100°C	ASTM D445	cSt	14.3
Viscosity @ 40°C	ASTM D445	cSt	91.4
Viscosity Index	ASTM D2270	None	162
Flash Point, minimum	ASTM D92	°C	230

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Radifleet or its distributors and agent for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.



Radifleet Sdn Bhd | Lot 137/138 Jalan 28/10A Taman Perindustrian IKS (MIEL) 68100 Kuala Lumpur | Tel: +60361871276 | [www.radifleet.com.my](http://www.radifleet.com.my)